

Darest SHOP

Cisco 927 Annex M over POTS and 1GE Sec



✓ Delivery time: 1-2 days

CHF **444.45**

CHF **411.15** excl.

Cisco 927 Annex M over POTS and 1GE Sec

Manufacturer [Cisco](#)
EAN 889728172165
Manufacturer# C927-4PM

Description

Cisco 927 Gigabit Ethernet security router with VDSL/ADSL2+ Annex M, 1.2 kg

Specification

Product Description	Cisco Integrated Services Router 927 - router - cable modem - desktop
Device Type	Router - cable modem - 4-port switch (integrated)
Enclosure Type	Desktop
Digital Signaling Protocol	VDSL, ADSL2+
WAN Ports Qty	2
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet

Network / Transport Protocol	L2TP, RSVP, ICMP/IP, IPSec, FTP, DHCP, DNS, L2TPv3, DDNS, RTP, HTTP, HTTPS, cRTP
Routing Protocol	OSPF, RIP-1, RIP-2, BGP, EIGRP, HSRP, VRRP, NHRP, IGMPv3, GRE, OSPFv3, policy-based routing (PBR), BGP-4+, WCCP, Bidirectional Forwarding Detection (BFD), RSVP, STP, MGRE
Remote Management Protocol	Telnet, SNMP 3, HTTP, HTTPS, SSH, CLI
Features	NAT support, auto-uplink (auto MDI/MDI-X), IGMP snooping, DiffServ support, MAC address filtering, LLQ, CBWFQ, WFQ, ACL support, QoS, LFI, DMVPN, DHCP server, VRF-Lite, DNS proxy, DHCP relay, DHCP client, MIB, NDP, VPN Server, FNF, DSCP support, Storm Control, SmartPort technology, VPN client, HQoS, SPAN, EEM, MHSRP, NBAR, NBAR 2, PfR, CBTS, CBTP, CBWRED, Cisco IP SLA, Cisco NG PnP Protocol
Compliant Standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1x
Power	DC 12 V
Dimensions (WxDxH)	25.91 cm x 17.78 cm x 2.8 cm
Manufacturer Warranty	1-year warranty

Techn. Details

Device Type	Router - 4-port switch (integrated)
Enclosure Type	Desktop
Connectivity Technology	Wired
Data Link Protocol	Ethernet, Fast Ethernet, Gigabit Ethernet
Network / Transport Protocol	L2TP, RSVP, ICMP/IP, IPSec, FTP, DHCP, DNS, L2TPv3, DDNS, RTP, HTTP, HTTPS, cRTP
Routing Protocol	OSPF, RIP-1, RIP-2, BGP, EIGRP, HSRP, VRRP, NHRP, IGMPv3, GRE, OSPFv3, policy-based routing (PBR), BGP-4+, WCCP, Bidirectional Forwarding Detection (BFD), RSVP, STP, MGRE
Remote Management Protocol	Telnet, SNMP 3, HTTP, HTTPS, SSH, CLI
Encryption Algorithm	DES, Triple DES, AES, SSL, PKI, 128-bit AES, 192-bit AES, 256-bit AES
Authentication	Secure Shell (SSH), RADIUS, TACACS+

Method

Features	NAT support, auto-uplink (auto MDI/MDI-X), IGMP snooping, DiffServ support, MAC address filtering, LLQ, CBWFQ, WFQ, ACL support, QoS, LFI, DMVPN, DHCP server, VRF-Lite, DNS proxy, DHCP relay, DHCP client, MIB, NDP, VPN Server, FNF, DSCP support, Storm Control, SmartPort technology, VPN client, HQoS, SPAN, EEM, MHSRP, NBAR, NBAR 2, PfR, CBTS, CBTP, CBWRED, Cisco IP SLA, Cisco NG PnP Protocol
Compliant Standards	IEEE 802.1D, IEEE 802.1Q, IEEE 802.1x, EN 61000-6-1, AS/NZS 60950-1, FCC CFR47 Part 15, UL 60950-1, IEC 60950-1, EN 60950-1, VCCI V-3, EN 61000-3-2:2006, EN 61000-3-3:2008, KN24, CNS13438:2006, EN 300 386 V1.6.1, CISPR 24:2010, EN 55024:2010, CISPR 22:2008, EN 300 386, TCVN 7189, EN 55032, CAN/CSA-C22.2 No. 60950-1, TCVN 7317, KN22:2009, ICES-003:2012 Issue 5
Processor	2.2 GHz
RAM	1 GB
Flash Memory	2 GB
Type	Cable modem
Digital Signaling Protocol	VDSL, ADSL2+
Protocols & Specifications	ITU G.992.5 Annex M
Interfaces	WAN: 1 x 10Base-T/100Base-TX/1000Base-T - RJ-45 WAN: 1 x VDSL / ADSL2+ LAN: 4 x 10Base-T/100Base-TX/1000Base-T - RJ-45 Management: 1 x console - RJ-45 USB 2.0: 1 x 4 pin USB Type A
Power Device	External power adapter - 30 Watt
Voltage Required	DC 12 V
OS Provided	Cisco IOS IP Base
Width	25.91 cm
Depth	17.78 cm
Height	2.8 cm
Service & Support	Limited warranty - advance parts replacement - 1 year - response time: 10 days
Min Operating Temperature	0 °C
Max Operating Temperature	45 °C
Humidity	5 - 95% (non-condensing)

Range
Operating

Related Prod.

ATX Power Supplies



Cisco - Power supply - 30 Watt



CHF **112.35**
CHF **103.93**
excl.

Date added: 2019-07-26 08:27:50 / SID: 1597782 / DID: 677RD93