

Darest SHOP

D-Link SWITCH 5 PORTS GIGABIT METALLIC



✓ Delivery time: 1-2 days

CHF **21.65**

CHF **20.03** excl.

SWITCH 5 PORTS GIGABIT METALLIC NMS IN CPNT

Manufacturer [D-Link](#)
EAN 0790069458576
Manufacturer# DGS-105GL/E

Description

D-Link DGS-105GL/E. Switch-Typ: Unmanaged. Basic Switching RJ-45 Ethernet Ports-Typ: Gigabit Ethernet (10/100/1000), Anzahl der basisschaltenden RJ-45 Ethernet Ports: 5. MAC-Adressentabelle: 2000 Eintragungen, Routing-/Switching-Kapazität: 10 Gbit/s. Netzstandard: IEEE 802.3, IEEE 802.3ab, IEEE 802.3az, IEEE 802.3p, IEEE 802.3u, IEEE 802.3x. DC input Spannung: 5 V. Netzstecker: DC-Anschluss

Specification

Product Description	D-Link DGS 105GL - switch - 5 ports - unmanaged
Device Type	Switch - 5 ports - unmanaged
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000
Performance	Switching capacity: 10 Gbps Packet filter/forwarding rate (10 Mbps): 14880 pps Packet filter/forwarding rate (100 Mbps): 148800 pps Packet filter/forwarding rate (1000 Mbps):: 1488000

	pps
MAC Address Table Size	2K entries
Features	Flow control, auto-uplink (auto MDI/MDI-X), store and forward, QoS, D-Link Green Technology, fanless, metal housing, VoIP support, NAS support, SOHO, EEE
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
Dimensions (WxDxH)	10 cm x 6.7 cm x 2.4 cm
Weight	160 g
Localisation	Europe

Techn. Details

Device Type	Switch - 5 ports - unmanaged
Enclosure Type	Desktop
Subtype	Gigabit Ethernet
Ports	5 x 10/100/1000
Performance	Switching capacity: 10 Gbps Packet filter/forwarding rate (10 Mbps): 14880 pps Packet filter/forwarding rate (100 Mbps): 148800 pps Packet filter/forwarding rate (1000 Mbps):: 1488000 pps
MAC Address Table Size	2K entries
Features	Flow control, auto-uplink (auto MDI/MDI-X), store and forward, QoS, D-Link Green Technology, fanless, metal housing, VoIP support, NAS support, SOHO, EEE
Compliant Standards	IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.1p, IEEE 802.3x, IEEE 802.3az
Status Indicators	Power, link/activity
Interfaces	5 x 1000Base-T RJ-45
Power Device	External power adapter
Power Provided	DC 5 V - 1 A
Power Consumption Operational	3.55 Watt

MTBF	1,455,562 hours
Compliant Standards	Plug and Play, FCC, RoHS
Localisation	Europe
Width	10 cm
Depth	6.7 cm
Height	2.4 cm
Weight	160 g
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	10 - 90% (non-condensing)
Min Storage Temperature	-10 °C
Max Storage Temperature	70 °C
Humidity Range Storage	5 - 95% (non-condensing)

Related Prod.

Cat 6a Cables (6)

	Wirewin Slim Light - Patch cable - RJ-45 (M) to RJ-45 (M) - 2 m - U/FTP - CAT 6a - molded, round - white	CHF 10.85 CHF 10.04 excl.
	Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 1.5 m - U/FTP - CAT 6a - molded, flat - grey	CHF 9.55 CHF 8.83 excl.
	Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 25 cm - U/FTP - CAT 6a - molded, flat - red	CHF 6.35 CHF 5.87 excl.

Cat 6 Cables

	Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 1 m - STP - CAT 6 - booted, flat - violet	CHF 8.45 CHF 7.82 excl.
	Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 5 m - STP - CAT 6 - molded, snagless, flat - blue	CHF 13.30 CHF 12.30



Wirewin Slim - Patch cable - RJ-45 (M) to RJ-45 (M) - 10
m - STP - CAT 6 - booted, flat - black



excl.

CHF **21.05**

CHF **19.47**

excl.

Date added: 2021-01-24 08:18:45 / SID: 2014322 / DID: 21.14.2091