

Darest SHOP

Cisco Firepower 1120 ASA



? Next possible delivery date: May 26, 2024

CHF **2,059.85**

CHF **1,905.50** excl.

CISCO Firepower 1120 ASA Appliance, CISCO Firepower 1120 ASA Appliance, 1U

Manufacturer [Cisco](#)
EAN 0889728192590
Manufacturer# FPR1120-ASA-K9

Description

Firepower 1120 ASA Appliance 1U, 4.37 x 26.87 x 43.69 cm

Specification

Product Description	Cisco FirePOWER 1120 ASA - firewall
Device Type	Firewall
Form Factor	Rack-mountable - 1U
Hard Drive	200 GB x 1
Performance	Firewall throughput (UDP): 4.5 Gbps Multiprotocol firewall throughput: 2.5 Gbps IPsec VPN throughput (450B UDP L2L test): 1 Gbps
Capacity	Concurrent connections: 200000 New connections per second: 75000 VPN peers: 150 Security contexts: 2

Included Accessories	Mounting brackets
Power	AC 120/230 V (50/60 Hz)
Dimensions (WxDxH)	43.7 cm x 26.9 cm x 4.37 cm
Weight	3.63 kg
Manufacturer Warranty	90 days warranty

Techn. Details

Device Type	Firewall
Height (Rack Units)	1U
Width	43.7 cm
Depth	26.9 cm
Height	4.37 cm
Weight	3.63 kg
Hard Drive	200 GB x 1
Form Factor	Rack-mountable
Connectivity Technology	Wired
Performance	Firewall throughput (UDP): 4.5 Gbps Multiprotocol firewall throughput: 2.5 Gbps IPsec VPN throughput (450B UDP L2L test): 1 Gbps
Capacity	Concurrent connections: 200000 New connections per second: 75000 VPN peers: 150 Security contexts: 2
Features	1 fan
Interfaces	8 x - RJ-45 4 x - SFP (mini-GBIC) 1 x 1000Base-T (management) - RJ-45 1 x serial - RJ-45 1 x USB 3.0 - Type A
Included Accessories	Mounting brackets
Compliant Standards	CISPR 22 Class A, CISPR 24, EN 61000-3-2, EN 61000-3-3, EN55024, AS/NZS 60950-1, EN 61000-4-4, EN 61000-4-2, EN 61000-4-3, EN 61000-4-6, ICES-003 Class A, EN 61000-4-5, EN 61000-4-11, EN 61000-4-8, UL 60950-1, IEC 60950-1, EN 60950-1, GB 4943, Directive 2004/108/EC, VCCI Class A, KN24, KN22 Class A, EN 55022 Class A, FCC CFR47 Part 15 A, CNS 13438 Class A, EN 300 386, TVCN 7317, Directive 2006/108/EC, TCVN 7189, CAN/CSA-C22.2 No. 60950-1, AS/NZS CISPR22 Class A

Power Device	Internal power supply
Voltage Required	AC 120/230 V (50/60 Hz)
Service & Support	Limited warranty - advance hardware replacement - 90 days - response time: 10 days
Min Operating Temperature	0 °C
Max Operating Temperature	40 °C
Humidity Range Operating	90% (non-condensing)

Related Prod.

Copper Transceivers



Cisco - SFP (mini-GBIC) transceiver module - Gigabit Ethernet - 1000Base-T - RJ-45 - for Cisco 20-port 1-Gigabit; Nexus 7700 F3-Series, 9372PX, 9396PX

CHF **247.25**

CHF **228.72**

excl.



Server Accessories



CISCO Firepower 1K Series Rackmount Brac, CISCO Firepower 1K Series Rackmount Brackets FPR-1120/1140

CHF **80.50**

CHF **74.47**

excl.



Power Cables



Cisco - Power cable - Europe

CHF **48.45**



CHF **44.82**

excl.



Cisco - Power cable - Component (Networking) - Europe - for Cisco 4000, WS-C1400; Catalyst 1200, 1700, 2000, 2940, 2960, 3560; FastHub 100

CHF **46.70**

CHF **43.20**

excl.

