

Darest SHOP

Lexmark



? Next possible delivery date: May 16, 2024

CHF **54.75**

CHF **50.65** excl.

Marknet N8352 802.11 b/g/n Wireless Printserver with NFC

Manufacturer	Lexmark
EAN	734646568975
Manufacturer#	27X0135

Description

Place assets where they are needed - printer location is functionally and economically driven, not constrained by existing LAN connections. SNMPv3 supports encrypted and authenticated management traffic protecting remote configuration and device status messages. IPSec can be used with both TCP/IP IPv4 and IPv6 networks and provides encryption and authentication of communications at the network layer.

Specification

Product Description	Lexmark MarkNet N8352 - print server - USB
Device Type	Print server
Form Factor	External
Interface (Bus) Type	USB
Dimensions	15.2 cm x 22.9 cm x 4.1 cm

(WxDxH)

Weight	170 g
Data Link Protocol	802.11b/g/n, NFC
Data Transfer Rate	72 Mbps
Network / Transport Protocol	TCP/IP, UDP/IP, NTP, ICMP/IP, IPSec, LPR/LPD, ARP, FTP, BOOTP, DHCP, DNS, RARP, SLP, DDNS
Frequency Band	2.4 GHz
Compliant Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11n
System Requirements	HP-UX 11.11, Novell NetWare 6.5, Novell NetWare 5.1 SP6 or later, Novell NetWare 6.0 SP3 or later, HP-UX 11.23, Microsoft Windows 7, IBM AIX 5.3, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, Microsoft Windows Vista, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, Apple MacOS X 10.6, SUSE Linux Enterprise Desktop 11, Microsoft Windows 7 64-bit Edition, Red Flag Linux 6.0, Debian GNU/Linux 5.0, SUSE Linux Enterprise Desktop 10, SuSE Linux Enterprise Server 10, Microsoft Windows Vista (64-bit versions), Red Hat Enterprise Linux WS 5, Microsoft Windows Server 2008, IBM AIX 6.1, Microsoft Windows Server 2008 x64 Edition, HP-UX 11.31, Linux Linpus Desktop 9.6, SunSoft Solaris SPARC Platform Edition 9, SunSoft Solaris SPARC Platform Edition 10, Apple MacOS X Lion 10.7, openSUSE 11.4, Windows 8, IBM AIX 7.1, Linux Mint 11, SunSoft Solaris x86 11, Debian GNU/Linux 6.0, Linux Mint 10, Red Hat Enterprise Linux WS 6, Ubuntu 12.04, Apple OS X 10.8 Mountain Lion, openSUSE 12.2, Windows 8 64-bit Edition, openSUSE 12.1, Linux Mint 12, SunSoft Solaris SPARC Platform Edition 11, Red Hat Fedora 17, Android 4.1.2 (Jelly Bean), Ubuntu 12.10, Android 4.2.2 (Jelly Bean), Android 4.3 (Jelly Bean), Windows 8.1 64-bit Edition, Microsoft Windows Server 2012 R2, Windows 8.1, Windows RT, Apple OS X 10.9 Mavericks, Red Hat Fedora 18, Linux Mint 13, PCLinuxOS 2011, Android 4.4.2 (KitKat), Microsoft Windows RT 8.1, Red Hat Fedora 19, Apple MacOS X 10.10, Apple iOS 4.2
Designed For	Lexmark C2425, C2535, CS310, CS317, CS410, CS417, CS421, CS510, CS517, CS521, CS622, CX310, CX317, CX410, CX417, CX421, CX510, CX517, CX522, CX622, CX625, MS310, MS312, MS315, MS317, MS410, MS415, MS417, MS510, MS517, MS610, MS617, MX310, MX317, MX410, MX417

Techn. Details

Device Type	Print server
Form Factor	External
Interface (Bus) Type	USB
Connectivity Technology	Wireless

Data Link Protocol	IEEE 802.11b, IEEE 802.11g, IEEE 802.11n, NFC
Data Transfer Rate	72 Mbps
Network / Transport Protocol	TCP/IP, UDP/IP, NTP, ICMP/IP, IPSec, LPR/LPD, ARP, FTP, BOOTP, DHCP, DNS, RARP, SLP, DDNS
Remote Management Protocol	SNMP 1, Telnet, SNMP 3, SNMP 2c, HTTP, HTTPS, TFTP, IPP 1.0, IPP 1.1, IPP 2.0
Frequency Band	2.4 GHz
Compliant Standards	IEEE 802.11b, IEEE 802.11g, IEEE 802.1x, IEEE 802.11i, IEEE 802.11n
Cables Included	1 x USB cable
Encryption Algorithm	LEAP, MD5, 128-bit WEP, 64-bit WEP, TLS, PEAP, TTLS, WPA2, WPA2-Enterprise
OS Required	HP-UX 11.11, Novell NetWare 6.5, Novell NetWare 5.1 SP6 or later, Novell NetWare 6.0 SP3 or later, HP-UX 11.23, Microsoft Windows 7, IBM AIX 5.3, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, Microsoft Windows Vista, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, Apple MacOS X 10.6, SUSE Linux Enterprise Desktop 11, Microsoft Windows 7 64-bit Edition, Red Flag Linux 6.0, Debian GNU/Linux 5.0, SUSE Linux Enterprise Desktop 10, SuSE Linux Enterprise Server 10, Microsoft Windows Vista (64-bit versions), Red Hat Enterprise Linux WS 5, Microsoft Windows Server 2008, IBM AIX 6.1, Microsoft Windows Server 2008 x64 Edition, HP-UX 11.31, Linux Linpus Desktop 9.6, SunSoft Solaris SPARC Platform Edition 9, SunSoft Solaris SPARC Platform Edition 10, Apple MacOS X Lion 10.7, openSUSE 11.4, Windows 8, IBM AIX 7.1, Linux Mint 11, SunSoft Solaris x86 11, Debian GNU/Linux 6.0, Linux Mint 10, Red Hat Enterprise Linux WS 6, Ubuntu 12.04, Apple OS X 10.8 Mountain Lion, openSUSE 12.2, Windows 8 64-bit Edition, openSUSE 12.1, Linux Mint 12, SunSoft Solaris SPARC Platform Edition 11, Red Hat Fedora 17, Android 4.1.2 (Jelly Bean), Ubuntu 12.10, Android 4.2.2 (Jelly Bean), Android 4.3 (Jelly Bean), Windows 8.1 64-bit Edition, Microsoft Windows Server 2012 R2, Windows 8.1, Windows RT, Apple OS X 10.9 Mavericks, Red Hat Fedora 18, Linux Mint 13, PCLinuxOS 2011, Android 4.4.2 (KitKat), Microsoft Windows RT 8.1, Red Hat Fedora 19, Apple MacOS X 10.10, Apple iOS 4.2
Width	15.2 cm
Depth	22.9 cm
Height	4.1 cm
Weight	170 g
Min Operating Temperature	16 °C

Max Operating Temperature	32 °C
Humidity Range Operating	8 - 80%
Designed For	Lexmark C2425dw, C2535dw, CS310dn, CS310n, CS317dn, CS410dn, CS410dtn, CS410n, CS417dn, CS421dn, CS510de, CS510dte, CS517de, CS521dn, CS622de, CX310dn, CX310n, CX317dn, CX410de, CX410de DSV EG, CX410dte, CX410e, CX410e Gov S36, CX417de, CX421adn, CX510de, CX510de SPR Columbia, CX510de Statoil, CX510dhe, CX510dthe, CX517de, CX522ade, CX622ade, CX625ade, CX625adhe, MS310dn, MS312dn, MS315dn, MS317dn, MS410dn, MS415dn, MS417dn, MS510dn, MS510dtn, MS517dn, MS610de, MS610dn, MS610dte, MS617dn, MX310dn, MX317dn, MX410de, MX417de

Date added: 2015-02-13 08:22:37 / SID: 1112513 / DID: 2695323