

Dareest SHOP

ASUS ZenDrive U9M - SDRW-08U9M-U



✓ Delivery time: 1-2 days

CHF **40.15**

CHF **37.14** excl.

ASUS ZenDrive U9M SDRW-08U9M-U - Disk drive - DVD±RW (±R DL) - 8x/8x - USB 2.0 - external - black

Manufacturer	Asus
EAN	4712900714579
Manufacturer#	90DD02A0-M29000

Description

External, 5.25" / USB2.0 / BD-R 6x, BD-ROM 6x, DVD+/-R 8x,DVD+RW 8x,-RW 6x, CD-R 24x / Power2Go

Specification

Product Description	ASUS ZenDrive U9M SDRW-08U9M-U - DVD±RW (±R DL) drive - USB 2.0 - external
Device Type	DVD±RW (±R DL) drive - external
Colour	Black
Interface	USB 2.0
Dimensions (WxDxH)	13.55 cm x 14.25 cm x 1.39 cm
Weight	245 g

Optical Storage	DVD±RW (±R DL)
Read Speed	24x (CD) / 8x (DVD)
Write Speed	24x (CD) / 8x (DVD±R) / 6x (DVD±R DL)
CD / DVD Rewrite Speed	24x (CD) / 6x (DVD-RW) / 8x (DVD+RW)
Designed For	ASUSPRO P1; 14; 15; ROG Strix G GL531GU; ROG Strix G15; G17; ROG Strix SCAR 17; ROG Zephyrus Duo 15; ROG Zephyrus G14; S17; TUF Gaming A15; A17; F15; F17; FX505DT; FX705DT; FX705DY; TUF505DV; VivoBook 14; 15; 17; VivoBook Flip 12 TP202NA; 14 TP401MA; X543UA; ZenBook 13; 14

Techn. Details

Device Type	DVD±RW (±R DL) drive - external
Colour	Black
Interface	USB 2.0
Width	13.55 cm
Depth	14.25 cm
Height	1.39 cm
Weight	245 g
Type	DVD±RW (±R DL)
Read Speed	24x (CD) / 8x (DVD)
Write Speed	24x (CD) / 8x (DVD±R) / 6x (DVD±R DL)
CD / DVD Rewrite Speed	24x (CD) / 6x (DVD-RW) / 8x (DVD+RW)
Supported Recording Modes	Multisession, disc-at-once, track-at-once, packet writing, session-at-once, restricted overwrite, random access write, incremental recording, sequential write
Supported Media Formats	CD Text, CD Extra, CD-DA (audio), CD-I, CD-ROM XA, Photo CD, CD-ROM, DVD-Video
Supported Media Types	CD-ROM, CD-R, CD-RW, DVD-ROM, DVD-R, DVD-RW, DVD+RW, DVD+R, DVD+R DL, DVD-R DL, M-DISC
Access Time	160 ms (DVD), 140 ms (CD)

Features	E-Green Engine technology, Disc Encryption
Cables Included	Mini-USB to USB Y-cable ¦ Mini-USB to USB-C cable
Software Included	NERO BackItUp, CyberLink PowerBackup 2.5, E-Green, CyberLink Power2Go 8
OS Required	Apple MacOS X 10.6 or later, Microsoft Windows XP / Vista / 7 / 8 / 8.1 / 10
System Requirements Details	Pentium 4 - 2 GHz - RAM: 512 MB
Min Operating Temperature	5 °C
Max Operating Temperature	40 °C
Humidity Range Operating	15 - 80% (non-condensing)
Designed For	ASUSPRO P1 P1440FA-C53P ¦ ASUS 14 X409JA-EK026T ¦ ASUS 15 M509BA-EJ183T, M509DA-EJ025, M509DA-EJ1062T, S509DA-EJ029T ¦ ASUS ROG Strix G GL531GU WB53 ¦ ASUS ROG Strix G15 G512LU-AL041T, G512LW-WS74 ¦ ASUS ROG Strix G17 G712LU-H7015T, G712LU-H7023T, G712LV-EV023T, G712LV-H7074T, G712LV-H7077T ¦ ASUS ROG Strix SCAR 17 G732LV-EV029T, G732LWS-HG029T, G732LXS-HG014R, G732LXS-XS94 ¦ ASUS ROG Zephyrus Duo 15 GX550LWS-32T, GX550LWS-HC037T, GX550LXS-XS96 ¦ ASUS ROG Zephyrus G14 GA401II-025T, GA401II-HE092T, GA401II-HE109T, GA401IU-HE002 ¦ ASUS ROG Zephyrus S17 GX701LWS-EV029T, GX701LWS-EV076T, GX701LWS-HG052R, GX701LXS-HG007T ¦ ASUS TUF Gaming A15 FX506II-HN111T, FX506IU-HN222T, FX506IU-HN296T ¦ ASUS TUF Gaming A17 FX706II-AU031T ¦ ASUS TUF Gaming F15 FX506IH-BQ224T, FX506LH-BQ030, FX506LH-HN111T, FX506LI-BQ052T, FX506LI-HN023T, FX506LI-HN222T, FX506LU-HN037T, FX506LU-HN333T ¦ ASUS TUF Gaming F17 FX706LI-AU022T, FX706LI-H7010T ¦ ASUS TUF Gaming FX505DT BQ137T, HN549T, HN571T ¦ ASUS TUF Gaming FX705DT ¦ ASUS TUF Gaming FX705DY ¦ ASUS TUF505DV HN232T ¦ ASUS VivoBook 14 K413FA-EK695T, M413IA-EB371T ¦ ASUS VivoBook 15 F512JA-EJ011T, X512DA-EJ1458T, X512FB-BR468T, X512FJ-EJ529T, X512JA-BQ147T ¦ ASUS VivoBook 17 M712DA-AU311T, X712FA-AU606R, X712FA-AU642T, X712FA-AU643T, X712FA-AU848T ¦ ASUS VivoBook Flip 12 TP202NA CMSP, QMSP, XS04 ¦ ASUS VivoBook Flip 14 TP401MA CMSP, QMSP ¦ ASUS X543UA GO3047T, GQ2636T ¦ ASUS ZenBook 13 ¦ ASUS ZenBook 14

Date added: 2020-04-23 08:13:03 / SID: 1890334 / DID: ASU-90DD02A0-M29000