Epson Matrixprinter LQ-630 Parallel / USB 24-pin

❓ Next possible delivery date: May 24, 2024

CHF **506.85**

CHF **468.87** excl.

Matrixprinter LQ-630 Parallel / USB 24-pin (2x12)

Manufacturer	Epson
EAN	8715946538068
Manufacturer#	C11C480141

Description

Matrixprinter LQ-630; Parallel / USB; 24-pin (2x12)

Specification

Product Description	Epson LQ 630 - printer - B/W - dot-matrix
Printer Type	Personal printer - dot-matrix - 24 pin - B/W
Weight	3.5 kg
Max Media Size (Custom)	257 mm x 559 mm
Print Speed	Up to 300 char/sec - fast draft ¦ Up to 360 char/sec - fast draft ¦ Up to 225 char/sec - draft ¦ Up to 79 char/sec - laser quality
Max Resolution	360 x 180 dpi

(B&W)	
Interface	Parallel, USB 2.0
RAM Installed (Max)	32 KB
Language Simulation	EPSON ESC/P 2, IBM PPDS
Media Type	Labels, plain paper, continuous forms
System Requirements	Microsoft Windows 98, Microsoft Windows 2000, Microsoft Windows XP, Microsoft Windows 7, Windows 8
Manufacturer Warranty	1-year warranty
Dimensions (WxDxH)	38.6 cm x 30.6 cm x 18.5 cm

Techn. Details

Printer Type	Personal printer - dot-matrix - 24 pin - monochrome
Print Speed	Up to 300 char/sec - fast draft - 10 cpi ¦ Up to 360 char/sec - fast draft - 12 cpi ¦ Up to 225 char/sec - draft - 10 cpi ¦ Up to 79 char/sec - laser quality - 10 cpi
Connectivity Technology	Wired
Interface	Parallel, USB 2.0
Max Resolution (B&W)	360 x 180 dpi
Language Simulation	EPSON ESC/P 2, IBM PPDS
RAM Installed (Max)	32 KB
Media Type	Labels, plain paper, continuous forms
Max Media Size (Custom)	257 mm x 559 mm
Max Sheets in Multi-Part Form	5
Connections	1 x USB 2.0 - 4 pin USB Type B ¦ 1 x parallel
Consumables Included	1 x ribbon (black) - up to 2 million characters
MTBF	10,000 hour(s)

Power Consumption Operational	20 Watt
Power Consumption Stand by	4.8 Watt
Software Included	Drivers & Utilities, EPSON Status Monitor
OS Required	Microsoft Windows 98, Microsoft Windows 2000, Microsoft Windows XP, Microsoft Windows 7, Windows 8
Service & Support	Limited warranty - 1 year - carry-in
Min Operating Temperature	5 °C
Max Operating Temperature	35 °C
Humidity Range Operating	10 - 80%
Sound Emission (Operating)	57 dBA
Width	38.6 cm
Depth	30.6 cm
Height	18.5 cm
Weight	3.5 kg
Width (Shipping)	31 cm
Depth (Shipping)	45.5 cm
Height (Shipping)	26.5 cm
Weight (Shipping)	5.2 kg