

Darest SHOP

Lexmark Matrixdrucker 2591 24 Nadeln, A3 Parallel, USB



? Next possible delivery date: May 2, 2024

CHF **932.60**

CHF **862.72** excl.

Matrixdrucker 2591 24 Nadeln, A3 Parallel, USB 2.0, USB Port

Manufacturer	Lexmark
EAN	734646347594
Manufacturer#	11C2980

Description

The Lexmark Forms Printer 2591+ provides high-quality forms printing and features such as high-yield ribbons, multi-font document support and character and page monitoring.

Specification

Product Description	Lexmark Forms Printer 2591+ - printer - B/W - dot-matrix
Printer Type	Workgroup printer - dot-matrix - 24 pin - B/W
Weight	9.8 kg
Max Media Size	420 x 559 mm
Min Media Size (Custom)	76 mm x 76 mm

Max Media Size (Custom)	420 mm x 559 mm
Print Speed	Up to 556 char/sec - fast draft ¦ Up to 480 char/sec - draft ¦ Up to 160 char/sec - near letter
Max Resolution (B&W)	360 x 360 dpi
Interface	Parallel, USB
RAM Installed (Max)	512 KB
Language Simulation	IBM PPDS, EPSON
Barcodes	Industrial 2 of 5, NW-7, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Code 3 of 9, Interleaved 2 of 5, Postnet
Media Type	Plain paper, continuous forms
Media Handling	Front paper feeder
System Requirements	Microsoft Windows 2000, SunSoft Solaris 8, IBM AIX 5.2, IBM AIX 5.1, HP-UX 11.11, SunSoft Solaris 9, SuSE Linux Enterprise Server 8, Red Hat Enterprise Linux WS 3, SunSoft Solaris 10, IBM AIX 5.3, SuSE Linux Enterprise Server 9, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, SuSE Linux 10.0, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, SuSE Linux 10.1, Debian GNU/Linux 3.1, SuSE Linux Enterprise Server 10, Red Hat Enterprise Linux WS 5, SuSE Linux 10.2, Debian GNU/Linux 4.0, Linspire 5.0, Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits)
Manufacturer Warranty	2-year warranty
Dimensions (WxDxH)	63.4 cm x 29 cm x 19.5 cm

Techn. Details

Printer Type	Workgroup printer - dot-matrix - 24 pin - monochrome
Print Speed	Up to 556 char/sec - fast draft - 12 cpi ¦ Up to 480 char/sec - draft - 12 cpi ¦ Up to 160 char/sec - near letter - 12 cpi
Connectivity Technology	Wired
Interface	Parallel, USB
Max Resolution	360 x 360 dpi

(B&W)

Language Simulation	IBM PPDS, EPSON
Barcodes	Industrial 2 of 5, NW-7, EAN/JAN-8, EAN/JAN-13, UPC-A, UPC-E, Codabar, Code 128, Code 3 of 9, Interleaved 2 of 5, Postnet
Media Handling	Front paper feeder
RAM Installed (Max)	512 KB
Media Type	Plain paper, continuous forms
Max Media Size	420 x 559 mm
Min Media Size (Custom)	76 mm x 76 mm
Max Media Size (Custom)	420 mm x 559 mm
Media Sizes	420 x 559 mm, 76 x 76 mm
Media Weight	60 g/m ² - 90 g/m ²
Max Sheets in Multi-Part Form	6
Connections	1 x USB - 4 pin USB Type B 1 x parallel - 36 PIN Centronics
Consumables Included	1 x ribbon (black) - up to 4 million characters
MTBF	12,500 hour(s)
Compliant Standards	FCC Class B certified, CSA, TUV GS, VCCI, C-Tick, SEMKO, CB, UL 60950-1, IEC 60950-1
Power Consumption Operational	50 Watt
Power Consumption Stand by / Sleep	4.2 Watt
OS Required	Microsoft Windows 2000, SunSoft Solaris 8, IBM AIX 5.2, IBM AIX 5.1, HP-UX 11.11, SunSoft

Solaris 9, SuSE Linux Enterprise Server 8, Red Hat Enterprise Linux WS 3, SunSoft Solaris 10, IBM AIX 5.3, SuSE Linux Enterprise Server 9, SunSoft Solaris x86 10, Red Hat Enterprise Linux WS 4, SuSE Linux 10.0, SuSE Linux Enterprise Server 11, Microsoft Windows Server 2008 R2, SuSE Linux 10.1, Debian GNU/Linux 3.1, SuSE Linux Enterprise Server 10, Red Hat Enterprise Linux WS 5, SuSE Linux 10.2, Debian GNU/Linux 4.0, Linspire 5.0, Microsoft Windows Vista (32/64 bits), Microsoft Windows 7 (32/64 bits), Microsoft Windows XP (32/64 bits), Microsoft Windows Server 2008 (32/64-bits), Microsoft Windows Server 2003 (32/64-bits)

ENERGY STAR	Yes
Service & Support	Limited warranty - 2 years - on-site - response time: next business day
Min Operating Temperature	10 °C
Max Operating Temperature	40 °C
Humidity Range Operating	8 - 90%
Sound Emission (Idle)	15 dBA
Sound Emission (Operating)	55 dBA
Width	63.4 cm
Depth	29 cm
Height	19.5 cm
Weight	9.8 kg
Width (Shipping)	75.1 cm
Depth (Shipping)	40.8 cm
Height (Shipping)	32.5 cm
Weight (Shipping)	12.3 kg

Related Prod.

Print Ribbons



Lexmark - Re-inking ribbon - 1 x black - 4 million characters - for Lexmark 23XX; Forms Printer 23XX, 24XX, 25XX



CHF **16.30**

CHF **15.08**
excl.



Lexmark - Re-inking ribbon - High Yield - 1 x black - 8 million characters - for Forms Printer 2480, 2481, 2490, 2491, 2580, 2581, 2590, 2591



CHF **27.70**

CHF **25.62**
excl.

Ethernet Print Servers



MarkNet N7000e (1 USB Port) 10/100 Ethernet, X560n/dn zu X644e/X646dte/X85x-Serie



CHF **352.00**

CHF **325.62**
excl.

Date added: 2012-01-20 08:35:28 / SID: 556557 / DID: 2691513